



## KWIK KLEEN

Kwik Kleen is a biodegradable, diluted form of Kwik Kleen Concentrate. This versatile product can be used for cleaning of:

- Oil and grease
- Dirt

Do not work in direct sunlight during hot weather. The ideal temperature should be 60° - 80°F (16° - 27°C).

Apply Kwik Kleen in a good ventilated area without excessive wind. Before using, review MSDS and wear proper gear.

When used as a degreaser, apply solution, let it soak, and if necessary, agitate the surface with soft sponge or similar to emulsify/solubilize; rinse with clean water. Reapply the solution as needed.

Note: Rinse off any residue of Kwik Kleen thoroughly, especially around intricate areas and, if applicable, apply extra rinse around headlights and taillights, plastic, and acrylic emblems.

### BENEFITS:

- 0.06 lb/gal (7.2 gm/liter) VOC
- Excellent general degreaser/cleaner
- HAPs-free
- Use as is
- Biodegradable
- Nonoffensive citrus odor
- Contains no ammonia or phosphates
- No flash point
- Environmentally safe

### APPLICATIONS:

Vehicle, equipment, and general purpose cleaning

- Trucking
- DOT
- Construction
- Mining
- AG
- Pipe
- Machine & Fabrication
- General Industrial

Due to the defatting effect on the skin, do not use Kwik Kleen as a hand cleaner.

TEST METHOD	DESCRIPTION	TYPICAL CHARACTERISTIC
EPA 1110	Corrosiveness	Pass - Not considered corrosive
OECD 301D	Biodegradability	Readily biodegradable
ASTM D-2243	Freeze and Thaw Stability, Cycles Passed	5
ASTM D-1475	Density	8.34 lb/gal (1.001 g/cm <sup>3</sup> )

*The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.*

### PACKAGING

260 Gallon Totes	55 Gallon Drums	5 Gallon Pails
---------------------	--------------------	-------------------

KATS Coatings is owned and operated by Ritek, Inc. We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RITEKS MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. RITEKS shall have no other liability with respect thereto. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. The information provided herein is based on technical data that Ritek, Inc. believes to be reliable. RITEKS, Inc. makes no representation or warranty as to the completeness or accuracy thereof and assumes no liability resulting from its use for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.

